



















Pods & Booths

Product Comparison













Spacestor.

Single User Pods & Booths

										
	Portals Open	Portals Quiet	Portals Connect	Portals Studio	Residence Work	Residence Max	Residence Connect	Residence Connect Accessible	Portico	
Product Code	PTP-SIS	PTP-SIG	PTC-DDA	PTS-SDP	PWP-GGB	PXP-SUP	PCN-SDP	PCN-ADA	PLT-SIT	
Clad Finish	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	White LPL/ HPL	
Upholstery Fabric	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified, subject to UL Listing	Camira/LUUM recommended palettes, or Camira, Kvadrat or LUUM as specified, subject to UL Listing and LRVs of fabrics being suited to optimum VC specification	Camira/LUUM recommended palettes, or Camira, Kvadrat or LUUM as specified, subject to UL Listing and LRVs of fabrics being suited to optimum VC specification	Dark Grey Acoustic Panels	
Desk	Fixed height, or electric height-adjustable for some models	Fixed height, or electric height-adjustable for some models	Electric height-adjustable & separately adjustable monitor	N/A	Fixed height for sitting or standing position	Fixed height or electric height-adjustable	Electric height-adjustable & separately adjustable monitor	Electric height-adjustable & separately adjustable monitor	Fixed height at sitting or standing position	
Monitor	N/A	N/A	Fully integrated, electric height-adjustable all-in-one PC	N/A	N/A	N/A	Fully integrated, electric height-adjustable all-in-one PC	Fully integrated, electric height-adjustable all-in-one PC	N/A	
Use Case	A semi-private touchdown space for users of all abilities	A private touchdown space for users of all abilities	A private video conferencing space optimised for virtual meetings	An accessible, customizable and space-efficient meeting space or single person workspace	Optimized for personal private focus - an individual working pod to escape the buzz	An enhanced ergonomic experience for individual focus work	A single-person, tech-integrated pod designed from the ground up for an optimal and inclusive virtual meeting experience with unparalleled acoustic properties	A single-person, tech-integrated pod designed from the ground up for an optimal and inclusive virtual meeting experience with unparalleled acoustic properties	All the essential features for focus, private working	
Acoustics	3 upholstered walls create a sound-absorbing cocoon around the user	3 upholstered walls create a sound-absorbing cocoon around the user with a magnetic seal door to reduce speech intelligibility	D _{sA} Rating 22.7dB - Class C Layers of foam and upholstery provide comfort acoustics, combined with a magnetic closure and drop-seal for speech privacy	3 upholstered walls with layers of foam and upholstery provide comfort acoustics, combined with a magnetic closure and drop-seal for speech privacy	Decibel reduction rating 29dB	Decibel reduction rating >35dB	Decibel reduction rating >35dB Layers of acoustic foam and upholstery combined with a drop seal on the door	Decibel reduction rating >35dB Layers of acoustic foam and upholstery combined with a drop seal on the door	Three acoustic walls and drop seal on door for increased privacy	
Ventilation	On some models: Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Four 7.2" fans - two static, two adjustable Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Fixed, PIR activated fan Speed: ≈ 900rpm Airflow: 58.6 CFM Static Pressure: 0.090mmH ₂ O	Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Adjustable 7.2" fan Speed: 400 - 1,500rpm Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Fixed, PIR activated fan	
Lighting	PIR activated LED light	PIR activated LED light	User-adjustable lighting with spotlights for focus work, and bias lighting with the light source located behind the monitor for the optimal on-screen experience	Six PIR activated LED lights	PIR activated LED light	Center LED spotlight	User adjustable bias lighting with light source located behind the monitor for optimal viewing experience	User adjustable bias lighting with light source located behind the monitor for optimal viewing experience	Two PIR activated LED lights	
Accessibility	No floor allows for easy accessibility. Widest variation is suitable for less ambulant users	No floor allows for easy accessibility	No floor allows for easy accessibility	ADA width door with level threshold for easy access	N/A	Level threshold for easy access	Level threshold for easy access	Designed for easy approach, entry and exit with a 810mm door clearance, level threshold and battery-powered push button door opener mechanism inside and out	No floor allows for easy accessibility	
Sustainability	FSC certified timber	FSC certified timber	FSC certified timber	FSC certified timber	FSC certified timber	FSC certified and 99% materials are LBC Red List Compliant	Materials palette is LBC Red List Compliant ensuring health, safety and comfort of users	Materials palette is LBC Red List Compliant ensuring health, safety and comfort of users	N/A	
UL Listing	N/A	N/A	N/A	N/A	N/A	UL Listed to 962 for both US & Canada	UL Listed to 962 for both US & Canada	UL Listed to 962 for both US & Canada	N/A	
Drawing & Dimensions	 w x d x h (inches) 52½" x 42" x 79¾"	 w x d x h (inches) 52½" x 42" x 79¾"	 w x d x h (inches) 47¾" x 71" x 88"	 w x d x h (inches) 100" x 71" x 88"	 w x d x h (inches) 40¾" x 38¼" x 86½"	 w x d x h (inches) 44¾" x 44¾" x 88"	 w x d x h (inches) 60" x 44¾" x 88"	 w x d x h (inches) 60" x 44¾" x 88"	 w x d x h (inches) 40" x 40" x 88"	
MEP Access	Easy sprinkler integration	Easy sprinkler integration	Easy sprinkler integration	Easy sprinkler integration. Additional removable internal wall panel for easy access to electrical components	Easy sprinkler integration	Easy sprinkler integration	Optional integral rear access chase for flexible connection of all MEP components	Optional integral rear access chase for flexible connection of all MEP components	Easy sprinkler integration	
Warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty View full Warranty Statement	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	5 year upholstery warranty 2 year moving parts warranty 1 year lights warranty	2 year moving parts warranty 1 year lights warranty

Collaborative Pods & Booths

					
	Railway Carriage	Portals Huddle	Portals Room	Residence Meet	Residence Huddle
Product Code	RYP-FAB	PTH-2PS	PTR-SDP	PMP-GGB	PHP-GGB
Clad Finish	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood	LPL/ HPL Birch Plywood
Upholstery Fabric	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified	Camira, Kvadrat or LUUM as specified
Desk	Fixed table with pole leg and additional disc base option	Fixed height at sitting position	N/A	Fixed height for sitting position or no desk	Fixed height for sitting position
Monitor	Option to add HD display monitor to back of booth	Option to add HD display monitor to back of booth	Integrated multi-fit screen bracket, customer supplies screen	N/A	N/A
Use Case	Optimized for collaborative in-person meetings of 2-6 people	Optimized for private collaborative in-person meetings of 2-4 people	A highly customizable, plug-and-play meeting space or single person office	Optimized for private 1-2-1 meetings, face-to-face	Optimized for private meetings, of two to four people face-to-face
Acoustics	3 upholstered walls create a sound-absorbing cocoon around the users	3 upholstered walls create a sound-absorbing cocoon around the users with a magnetic seal door with drop seal to reduce speech intelligibility	3 upholstered walls with layers of foam and upholstery provide comfort acoustics, combined with a magnetic closure and drop-seal for speech privacy	Decibel reduction rating 29dB	Decibel reduction rating 29dB
Ventilation	N/A	Adjustable: 3 x 7.2" fans Max Speed: 1500rpm Max Airflow: 140CFM	Adjustable: 6 x 7.2" fans Max Speed: 400 - 1,500rpm Max Airflow: 25CFM - 140CFM Static Pressure: 0.25mmH ₂ O - 3mmH ₂ O	Fixed, PIR activated fan Speed: ≈ 900rpm Airflow: 58.6 CFM Static Pressure: 0.090mmH ₂ O	Fixed, PIR activated fan Speed: ≈ 900rpm Airflow: 58.6 CFM Static Pressure: 0.090mmH ₂ O
Lighting	3 PIR activated lighting options: LED spotlight, strip lights, pendant	PIR activated spotlight	PIR activated spotlights	PIR activated LED light	PIR activated LED light
Accessibility	Optional to join extended table lengths allow for less ambulant users joining a meeting in a Railway Carriage	No floor allows for easy accessibility	ADA Door-width opening with level threshold for easy access	N/A	N/A
Sustainability	FSC certified timber	FSC certified timber	FSC certified timber	FSC certified timber	FSC certified timber
UL Listing	N/A	N/A	N/A	N/A	N/A
Drawing & Dimensions					
w x d x h (inches)	81" x 53¾" x 79¾"	81" x 42½" x 88"	109" x 100" x 88"	79" x 38¼" x 86½"	79" x 71" x 85"
MEP Access	Easy sprinkler integration	Easy sprinkler integration	Easy sprinkler integration. Additional removable internal wall panel for easy access to electrical components	Easy sprinkler integration	Easy sprinkler integration
Warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty	5 year upholstery warranty 1 year lights warranty

[View full Warranty Statement](#)

